

ANYSTREAM® HOTEL

S-2005-H



GENERAL SPECIFICATION

Water conserving pressure compensating Autoflo® device reduces flow to 2.5 GPM/9.46LPM maximum, to meet existing ASME A112.18.1/CSA B125.1 standard. Brass threaded inlet with ½" NPSM inlet. There is also a dual action combination spray.

S-2005-H

Polished chrome plated Anystream® Hotel Showerhead. Spray adjusting T-handle. 3½" face. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

S-2005-HB



S-2005-HB

Polished chrome plated Anystream® Hotel Showerhead. Spray adjusting T-handle. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

S-2005-HS



S-2005-HS

Polished chrome plated Anystream® Hotel Showerhead. Spray adjusting T-handle. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> E2	2.0 GPM flow rate (polished chrome finish only, not available on S-2005-HS)
<input type="checkbox"/> PB	Polished brass (S-2005-HB only)
<input type="checkbox"/> BN	Brushed nickel finish (S-2005-H & S-2005-HB only)
<input type="checkbox"/> BP	Blister pack packaging
<input type="checkbox"/> BC	Brushed chrome finish (S-2005-HB only)

This space for Architect/Engineer approval.

